



LEGEND

— 901 —	EXISTING CONTOUR
— 902 —	PROPOSED CONTOUR
— — —	EXISTING FENCE
- - - - -	PROPOSED OR RELOCATED FENCE
▬	PROPOSED BITUMINOUS SURFACE
□	NEW FACILITIES

NOTES:
 1. ALL SIDEWALKS TO BE 3'-0" WIDE x 3 1/2" THICK UNLESS SHOWN OTHERWISE. MAX. SLOPE ON SIDEWALK TO BE 5% IF GREATER CONTRACTOR TO INSTALL STEPS.

BENCHMARK
 SPIKE IN PP ACROSS STREET FROM TREATMENT PLANT 50' S.W. OF ENTRANCE. ELEV. 903.66

NO.	DATE	BY	REVISIONS
B	2-23-77	J.R.C.	REMOVED TWO M.H.'S - RENUMBERED REMAINING
A	7-6-76	J.R.C.	MISC. REVISIONS

DESIGNED K.L.V.	CHECKED K.L.V.
DRAWN J.R.C.	APPROVED W.H.M.
DATE 8/26/75	COMM.

I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY REGISTERED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA.
Karen L. Vax Carcken
 DATE Aug 29, 1975 REG. NO. 20159

McCOMBS-KNUTSON ASSOCIATES, INC.
 CONSULTING ENGINEERS ■ LAND SURVEYORS ■ SITE PLANNERS
 MINNEAPOLIS, HUTCHINSON and MARSHALL, MINNESOTA

WASTE WATER TREATMENT FACILITIES
 FOR
ELK RIVER, MINNESOTA

SCALE	AS NOTED
BOOK	PAGE
197	10
FILE NO.	2603

SITE GRADING PLAN

SHEET	REV.
3	B
OF	31